

**AX30**

## Admoveo SIP Paging Gateway

Admoveo AX30 SIP paging gateway is an SIP-enabled multi-functional IP audio device dedicated for industry users. It can convert voice streams from a SIP paging system or IPPBX system to analogue sounds for background music, public address, intercom, etc.

Based on the compact hardware design, open standard SIP protocol support, rich functionality, and high performance. Industry users can customize the AX30 SIP paging gateway into any desired form of intercom devices or paging speakers. With which can be widely used for smart and safe city applications, to increase the efficiency of communication and information sharing, as a result, to improve public safety and citizen welfare.

## Feature Highlights



### Built-in Amplifier

Built-in amplifier rated at 2x10W dual-channel output, passive loudspeakers can be connected directly for stereo audio output, no external amplifier is needed.



### Stereo Audio

Music can be streamed from Admoveo IP Audio Center using streamed media to the AX30 SIP paging gateway for local decoding and playback, high definition stereo audio quality is guaranteed.



### Two-way Intercom

Support 2 programmable "press-to-talk" switch buttons, with an external speaker and microphone, it can do two-way intercom calls for emergency or consulting purposes.



### HD Audio Codecs

Support G.722 wideband audio codec, provides clear and intelligible voice speech for the intercom calls. With the high audio reproduction ability and clarity, quality of communication is guaranteed.



### Compatible with Third-party SIP Server

With SIP protocol support, the AX30 SIP paging gateway can be easily integrated with existing third-party SIP servers. SIP paging or intercom calling using your existing phone system.



### Door Magnet Control

The AX30 SIP paging gateway is equipped with built-in relay switch, which can be used for door magnet control or other devices to be controlled with dry contact signal. The invoke of dry contact signal can be digital input signal from sensors, DTMF signal or call status.



### Automatic Control

The AX30 SIP paging gateways support processing the external sensor or other devices' digital input signal, to invoke dry contact signal output for door magnet control, automated emergency calling, automated emergency alarm, etc.




### Auto Provisioning

Admoveo IP Audio Center auto provisioning support, large-scale installations (local or remote) will be efficient and time-saving.



### Power over Ethernet (PoE)

Standard PoE (IEEE802.3at) support, sample and easy installation with a single network cable. Large-scale installation will be extremely easy and time-saving.



### Industrial Grade Standards

The AX30 SIP paging gateway is designed with industry standards which guaranteed its robustness and adaptability to outdoor harsh conditions from temperature -40°C to 75°C.



### Various Peripherals Support

Various peripherals can be integrated, like IP camera, smoke sensors, infrared sensors, door magnet, sound and light alarm which can be used for public safety and security purposes.

## Specifications

Audio Interfaces		AX30
Amplifier Output		2x10W, 8Ω (4 pins)
Headset Output		2x40mW, 16Ω (4 pins)
Microphone		2 pins Audio Input
Other Interfaces		
Power Input		DC 12-3A/24V-1.5A Jack and 2 pins DC 12-3A/24V-1.5A
Volume Control		VOL+ and VOL-, press both to announce IP address
Ethernet		ETH0+ETH1, 10/100Mbps, ETH0 with PoE IEEE 802.3at enabled
Call button		Support 2 call buttons (switch button)
Call button LED		Support 2 call button LED indicators
Digital level output		3.3V
Digital level input		5V Max
Dry Contact		NO/NC contacts, max AC 125V-1A, DC 60V-1A
Audio		
Audio Codecs		G.722, G.711 A-law, G.711 U-law, Opus
Music Streaming		MP3 sampling rate 8 – 48KHz, bit rate 64 – 320kbps, mono or Stereo
Protocols		
Protocols		SIP(RFC3261), HTTP, TCP/IP, SSL, DNS, SNTP, NTP, RTSP, RTP, RTCP, TCP, UDP, MQTT, ICMP, DHCP, ARP, SSH
Administration		
Configuration		Web interface or auto provisioning server
Provision method		MQTT IoT Protocol
Mechanical Properties		
Processor		ARM Cortex-A7
RAM		128MB DDR3
Storage		128MB SLC Flash
Environment		
Working Environment		-40°C ~ +75°C
Storage Environment		-40°C ~ +75°C
Humidity		10% ~ 95%RH Non-condensing
Other		
Dimension		153*76*33mm or 6.02*3*1.3in
Weight		400g
RST Key		Press and hold for 5 seconds to reset to factory defaults
LED Indicator		PWR power indicator, SYS system indicator